




NTN BEARUNG DRIVESHAFT,INC.



SKF SYK 20 TF bearing units

Bearing No. SYK 20 TF

Bore Diameter	20 mm
d	20 mm
s1	18,3 mm
A	32 mm
A1	21 mm
B	31 mm
G	10 mm
H	64 mm
H1	33,3 mm
H2	16 mm
J	96 mm
L	126 mm
N	17,5 mm
N1	12 mm
Weight	0,24 Kg
Basic dynamic load rating (C)	12,7 kN
Basic static load rating (C0)	6,55 kN
Fatigue load limit (Pu)	0,28
Category	Pillow Block Bearings
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	0.24
EAN	7316570402759
Product Group	M06110
Number of Mounting Holes	2

SYK 20 TF Bearing 2D drawings and 3D CAD models



NTN BEARUNG DRIVESHAFT,INC.

Mounting Method	Set Screw
Housing Style	2 Bolt Pillow Block
Rolling Element	Ball Bearing
Housing Material	Composite
Expansion / Non-expansion	Non-expansion
Mounting Bolts	10 Millimeter
Relubricatable	Yes
Insert Part Number	YAR 204-2F
Seals	M Seal
Housing Configuration	1 Piece Solid
Inch - Metric	Metric
Other Features	Single Row Y Bearing With Grub Screw
Long Description	2 Bolt Pillow Block; 20MM Bore; 33.3MM Base to Center Height; Set Screw Mount; Ball Bearing; Relubricatable; Composite; M Seal; Non-expansion
Category	Pillow Block
UNSPSC	31171511
Harmonized Tariff Code	8483.20.40.40
Noun	Bearing
Keyword String	Pillow Block
Manufacturer URL	http://www.skf.com
Manufacturer Item Number	SYK 20 TF
Weight / LBS	0.529
Nominal Bolt Center to Center	3.8 Inch 97 Millimeter
Base to Center Height	1.311 Inch 33.3 Millimeter
Bore	0.787 Inch 20 Millimeter
Bolt Spacing Minimum	0 Inch 0Millimeter
Bolt Spacing Maximum	0 Inch 0Millimeter
Length Thru Bore	1.22 Inch 31 Millimeter



NTN BEARUNG DRIVESHAFT,INC.

Actual Bolt Center to Center	3.8 Inch 96Millimeter
Housing material	Composite
A ₁	21 mm
A ₅	18.5 mm
B ₄	4.5 mm
H ₁	33.3 mm
H ₂	16 mm
J max.	101 mm
J min.	91 mm
N ₁	12.5 mm
s ₁	18.3 mm
Basic dynamic load rating C	12.7 kN
Basic static load rating C ₀	6.55 kN
Fatigue load limit P _u	0.28 kN
Limiting speed	8500 r/min
Mass bearing unit	0.24 kg
Thread grub screw G ₂	M6x0.75
Hexagonal key size for grub screw N	3 mm
Recommended tightening torque for grub screw	4 N · m
Recommended diameter for attachment bolts, mm G	10 mm
Recommended diameter for attachment bolts, inch G	0.375 in
Housing	SYK 504
Bearing	YAR 204-2F
End cover	ECY 204