



NTN BEARUNG DRIVESHAFT, INC.



6000 Bearing 2D drawings and 3D CAD models

6000 6001 6002 6003 6004 6005 6006 6007 6008
 6009 60010 6011 6012 6013 6014 6015 Distributor
 of SKF NSK Timken Koyo NACHI NTN Bearing,
 Bearings, Ball Be

Bearing No. 6000

| | |
|----------------------------------|------------------|
| Size | 10x26x8 mm |
| Bore Diameter | 10 mm |
| Outer Diameter | 26 mm |
| Width | 8 mm |
| d | 10 mm |
| D | 26 mm |
| B | 8 mm |
| C | 8 mm |
| r min. | 0.3 mm |
| da min. | 12 mm |
| Da max. | 24 mm |
| ra max. | 0.3 mm |
| Weight | 0.019 Kg |
| Basic dynamic load rating (C) | 4,55 kN |
| Basic static load rating (C0) | 1,97 kN |
| (Grease) Lubrication Speed | 30000 r/min |
| Enclosure | Open |
| Bore Type | Cylindrical Bore |
| Configuration | Single Row |
| Bore Size | 10 mm |
| Outside Diameter | 26 mm |
| Width | 8 mm |
| Fillet Radius/Chamfer | 0.3 mm |
| | |



NTN BEARUNG DRIVESHAFT,INC.

| | |
|-------------------------|-------------------|
| Dynamic Load Rating | 4,550 N |
| Static Load Rating | 1,970 N |
| Limiting Speed - Grease | 30,000 rpm |
| Limiting Speed - Oil | 36,000 rpm |
| Factor fo | 12.4 |
| Radial Clearance | 0.002 to 0.013 mm |
| da (min) | 12 mm |
| Da (max) | 24 mm |
| ra (max) | 0.3 mm |